

The **TW1000V-15G-115 Booster System** is equipped with a centrifugal pump regulated by a variable frequency drive that controls pump operation to maintain constant pressure regardless of varying demand or fluctuation in incoming pressure. This system will supply 15 GPM with a 115 PSI overboost.

### Features and Benefits:

- Residential & Commercial application
- Quiet, Compact & Powerful
- Variable Frequency Drive controlled pump
- Energy efficient operation
- Prewired & Factory Tested

### Standard system components:

- Centrifugal Pump
- VF drive with transducer
- Pneumatic tank
- Pressure Gauge
- Relief valve
- Tank tee
- Check valve
- Brass Nipple
- Steel Frame
- Copper Fittings




### Technical Specifications:

- Pump:** Goulds (TEFC motor) [3SV]
- Controller:** Emerson or equal
- Flow Rate:** 15 GPM
- Boost:** 115 PSI Overboost
- Horse Power:** 3 HP
- Suction:** 1 1/4 inch
- Discharge:** 1 1/4 inch
- Tank:** 8.5 Gallon
- Frame Size:** 18.75"W x 44.25"H x 16.25"D
- Decibel rating:** <70 db @ 3500 RPM
- Power Options:** Independent circuit required  
208-220V/1-3PH  
360-480V/3 PH

*All parts shown are included in the system  
Actual system components may vary  
Some assembly required*

*Pump performance curve*



### Minimum requirements:

- Adequate amount of water volume needed
- Water supply must be free of large impurities
- Booster system must not be run dry
- Pump needs flooded suction
- Pump cannot lift water from an underground water storage tank
- Booster system must be protected from the elements
- Isolation valves must be installed on suction and discharge of the booster system.