

The *TW3000H-210W-50 Triplex Booster System* is equipped with centrifugal pumps regulated by variable frequency drives that control pump operation to maintain constant pressure regardless of varying demand or fluctuation in incoming pressure. This system will supply 210 GPM with a 50 PSI overboost.

Features and Benefits:

- Commercial application
- Quiet, Compact & Powerful
- Variable Frequency Drive controlled pump
- Energy efficient operation
- Prewired & Factory Tested
- Lead/Lag & Alternation [Optional]
- BMS Compatibility [Optional]

Standard system components:

- Centrifugal Pumps
- VF drives
- Pressure transducers
- Disconnect boxes
- Pneumatic tank
- Pressure Gauges
- Relief valves
- Check valves
- Ball valves
- Steel frame

Technical Specifications:

Pump: Walrus (TEFC motor) [12T-4K]
Controller: Emerson or equal
Flow Rate: 210 GPM Total
Boost: 50 PSI Overboost
Horse Power: 3 HP Each
Manifolds: 4 inch
Tank: 2 x 26 Gallons [Flexcon]
Frame Size: 48.0"W x 60.0"H x 29.0"D
Decibel rating: <80 db @ 3500 RPM
Power Options: Independent circuit required
 208-220V/1-3PH
 360-480V/3 PH

Minimum requirements:

- Adequate amount of water volume needed
- Water supply must be free of large impurities
- Booster system must not be run dry
- Pump needs flooded suction
- Pump cannot lift water from an underground water storage tank
- Booster system must be protected from the elements
- Isolation valves must be installed on suction and discharge of the booster system.



*All parts shown are included in the system
 Actual system components may vary
 Some assembly required*

Performance curve for each pump

